



Technical Data Sheet

12.04

FAST Wall putty

PRODUCT DESCRIPTION

FAST water based Wall putty is a specialized product used to seal the pores, smoothness the surface by filling the porous, uneven spots and cracks. It decreases the paint consumption and gives the substrate a rich and smooth finish. Specialized binder combination strengthens the adhesion of the putty to the wall. FAST Wall Putty can be used on all types of concrete and plasters. FAST Wall putty is recommended to use only on interior surfaces. For use on exterior surfaces, please consult FAST technical Advisory Service.

TYPICAL PROPERTIES

• Pack Viscosity	120-140 GMCM @ Gel Strength @ 25 °C
• Specific Gravity	1.6 ~ 1.68
• pH	8.0 ~ 8.5
• VOC	< 50g/L
• Color	White
• Drying Time	02 ~ 03 Hours (Depends on Temperature and Humidity)
• Recoating Time	4 Hours Minimum (Depends on Temperature and Humidity)
• Coverage	05 ~06 m2 / Kg / Coat(Depends on Surface Porosity)
• Solvent / Cleaner	Water
• Flammability	Not Applicable
• Gloss	Matt

SURFACE PREPARATION

Surface must be free from dust, dirt, grease, oil, heavy shoot, chalk, mildew etc. Remove all old, flaking, loose paint to avoid adhesion problem.

New Surface Preparation:

- After Plastering, allow the surface to dry for minimum 12~15 weeks. Moisture contents must not exceed 15% in the plaster before application.
- After the wall is dry, apply one thin coat of FAST Plastron Primer and allow to dry for minimum 04 ~ 06 Hours.
- Apply the Project wall putty with suitable scrappers.

Old Surface Preparation:

- Wire-brush the surface to remove flaking, loose Paint.
- Scuff with suitable emery paper.
- Dust of the powder with dry brush.
- Apply one thin coat of FAST Plastron Prime rand allow to dry for 04 ~ 06 Hours
- Apply the Project wall putty with suitable scrapper.

APPLICATION INSTRUCTIONS

- For best results, apply 2~3 coats (Depends on surface porosity) of FAST Wall Putty with 06 ~ 08 Hours interval
- After proper drying, rub down with suitable emery paper to smoothen the surface.
- Do not dilute the product with water. It is available in "Ready to Use" packing.



➔ PRECAUTIONS

- Use protective equipment while application e.g. Apron, Gloves, Protective Glasses and Dust Mask.
- Ensure adequate ventilation during application.
- In case of Eye Splashes, wash with plenty of Fresh Water and consult medical advice.
- In case of skin contact, wash with plenty of water. In case of skin irritation (Sensitive Skin), obtain medical advice.
- In case of ingestion, do not induce vomiting. Drink plenty of Milk/Water and immediately consult a physician.
- Store the product below 40 °C and avoid direct sunlight for a longer period.
- As long as the container is firmly sealed, the material can be kept for 6-Months without deterioration.

FAST CHEM

