



9.04 FAST BITUFILL

FAST Curing Ready To Use Roads CrackFiller

DESCRIPTION:

FAST BITUFILL is an environmentally friendly prepared to utilize emulsified split filling compound. FAST Bitufill is a cold connected black-top emulsion treatment for broken black-top and splash fixed pavements.

As a water based polymer altered bitumen compound, FAST Bitufill is adaptable and quick drying, by and large empowering streets to be opened to activity without further re-do after application.

BENEFITS:

- Required no heating or special preparation, and is ready to use right out of the container.
- Repair crews save time by being able to grab and go without waiting for the material to be ready for application.
- Since no heating is required, you save money by not having to waste material. The safety and portability of FAST Bitufill make it the crack filler of choice.
- When properly applied FAST Bitufill can be driven over within 1 hour without tracking.
- No need for any technical persons for application, Normal labor can pour the material in to the crack.

SURFACE PREPARATION:

Prior to the application of the FAST Bitufill, all loose materials shall be removed from the surface and the same shall be cleaned by means of approved mechanical sweepers, blowers or brooms, until it is as free from dust which seems practicable.

APPLICATIONS:

Using the one gallon bottle, a pour pot or a drum pump pour FAST Bitufill is used as a percent % of length. Allow a few minutes for FAST Bitufill to seep completely down in to the crack. Being pouring grade material it travels in to the cracks without injection pump.

For cracks deeper than 2 inch, a second application of FAST Bitufill may be needed.

For urgent traffic opening adhesion promotion sand should be placed on treated cracks. This sand should be removed after 1 - 2 hours.





FastChem Constructions

The Fast Chemistry for Construction



PACKING:

5 Kg Bottle, 30, Kg Cane & 218 Kg Drum.

STORAGE:

FAST Bitufill should be kept within the range of 5 °C-50 °C

COVERAGE:

Approximate coverage rate is given below for 5 Kg Asphalt Crack Filler

TECHNICAL SERVICE:

A trained FastChem representative is available to assist in the preparation of specifications, and the resolution of concrete problems in the field.

WARRANTY:

This product is warranted to be free of defects in material and workmanship, and conform to FastChem Construction Chemicals ("FastChem") quality control standards. All recommendations, statements and technical data herein are based on tests we believe to be reliable and correct, but accuracy and completeness of said tests are not guaranteed and are not to be construed as a warranty or guaranty of any kind, expressed or implied including but not limited to, an implied warranty of merchantability or an implied warranty of fitness for a particular purpose. Satisfactory results depend upon many factors beyond FastChem's control. User shall rely on his or her own information and tests to determine suitability of the product for the intended use and user assumes all risk, loss, damage, expense and liability resulting from his or her direct use, indirect use or consequential to their use of the product. FastChem shall not be liable to the buyer or any third person for any injury, loss or damage directly or indirectly resulting from use or inability to use the product. FastChem's sole responsibility shall be to replace that portion of the product which proves to be defective. Any warranty claim must be made within six (6) months from the date of the claimed breach. This limited warranty applies only if the product was properly installed and used according to all instructions and was properly stored prior to use.

FastChem Technologies (Pvt) Ltd. Pakistan
Head Office Lahore:
20-A. Commercial Area Pak Arab Housing
Society Lahore.
Tel: 92(42)35803536 Mob: +92-322-4321261



المكتب لتشرق الأوسط
٤٠ أ، سوق، البحر، برج الخليفة،
دبي، متحدة عرب الامارات
رقم البريد: ٧٧١٧٨٤